



# BASELITE – SATELLITE – INC – SPECIFICATION SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

MODEL #	/	/	x	/	x	/	x	/	/	/	x	/	x	/	x
EXAMPLE:	SA1118	21P	-	-	-	75W	-	-	-	-	-	-	-	-	-

\*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:

---



---



---



SA118/21P/2-100INC

## A - SHADES

- SATELLITE**  
**SA8** - 100WINC (MAX)  
**SA18** - 2-100WINC (MAX)  
**SA118** - 2-100WINC (MAX)  
**SA24** - 2-100WINC (MAX)

## B - FINISH OPTIONS

- (SEE WEBSITE FOR SWATCH COLORS)  
 (\*SEE NOTES FOR LIMITATIONS\*)  
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

## C - MOUNTING OPTIONS

NOT AVAILABLE

## D - MOUNTING ADD-ONS

NOT AVAILABLE

## E - MOUNTING COLOR

NOT AVAILABLE

## F - LIGHT SOURCE

(SEE PAGE 4 FOR WATTAGE LIMITATIONS)  
**INCANDESCENT (INC)**  
 100W, 2-100W

## G - LED COLOR TEMP

SEE SECTION "B" FOR COLOR OPTIONS.

## H - ELECTRICAL OPTION

NOT AVAILABLE

## I - GLASS OPTIONS

NOT AVAILABLE

## J - ACCESSORIES


NOT AVAILABLE

## K - ACCESSORY COLOR


NOT AVAILABLE

## NOTES


- FINISH OPTIONS 75,76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
- FINISH OPTIONS 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
- FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
- COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.  
 \*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).  
 \*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.)  
 \*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.  
 \*FIXTURE DIMENSIONS MAY VARY ± 0.25.



**SA8** H-8.25" W-8"  
 \*FIXTURE COMES AS SHOWN  
 \*MOUNTING OPTIONS DO NOT APPLY



**SA118** H-20" W-18"  
 \*FIXTURE COMES AS SHOWN  
 \*MOUNTING OPTIONS DO NOT APPLY



**SA18** H-30" W-18"  
 \*FIXTURE COMES AS SHOWN  
 \*MOUNTING OPTIONS DO NOT APPLY



**SA24** H-30" W-24"  
 \*FIXTURE COMES AS SHOWN  
 \*MOUNTING OPTIONS DO NOT APPLY



# BASELITE – SATELLITE – INC – SPECIFICATION SHEET

PROJECT NAME: \_\_\_\_\_  
PROJECT TYPE: \_\_\_\_\_

## F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

INCANDESCENT (INC) <small>MED E26</small>						
<b>INC 100W (MAX) - SA8</b> <b>INC 2-100W (MAX) - SA18, SA118, SA24</b>			*IMPORTANT – FOR COMPACT FLUORESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE LEFT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING.  EXAMPLE: /CF42W /			
OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING	
INC100W	100W	PER BULB SPECS	>90	120-277 VAC	PER BULB SPECS	